



LensCoat® Canon RF 200-800 IS INSTRUCTIONS

Piece 1- Lens Hood Cover

Remove the lens hood cover from the lens. Carefully slide and stretch the lens cover into place.

Piece 2

Remove rotating collar foot for easier placement of piece 2-7, stretch and slide piece 2 down the lens to the lens section behind the front element.

Piece 3

Slide piece 3 down the lens to the zoom ring.

Piece 4

Slide piece 4 on to the zoom tension ring just behind the zoom ring.

Piece 5

Slide piece 5 down section with the lens controls, aligning the window with the lens controls. **For final placement pull the window for the slightly away from the lens and adjust to the left or right.**

Piece 6

Slide piece 6 on to the focus ring.

Piece 7

Slide piece 6 on to the section behind the focus ring.

Piece 8

Slide piece 8 on to the lens collar fitting the tripod foot and tension knob through the opening.

Piece 9

Slide piece 9 on to the rear of the lens.

Zoom Sleeve

The LensCoat kit for the Canon RF 100-500 IS includes an optional sleeve to cover the barrel that would be exposed when zooming. With the lens shade off carefully stretch the elastic over the front of the lens onto piece 2 and the end of the lens barrel. As you zoom in the sock will stretch and when it's zoomed out it will slightly bunch up.

LensCoat.com®
80 Throckmorton Street
Freehold, NJ 07728