



## **LensCoat® Sigma 150-600 Sport INSTRUCTIONS**

### ***Piece 1- Lens Hood Cover***

Remove the lens hood cover from the lens. Carefully slide and stretch the lens cover into place.

***When looping the pieces around the lens foot remember to invert them so they have the correct orientation once flipped over the lens***

### ***Piece 2***

Stretch and slide piece 2 down the lens to just after the zoom ring.

### ***Piece 3***

Slide piece 3 down the lens to the zoom ring.

### ***Piece 4***

Carefully slide piece 4 it down the lens just after the focus ring. **Lining up the window for the zoom lock.**

### ***Piece 5***

Slide piece 5 it down to the focus ring.

### ***Piece 6***

Carefully slide piece 6 it down the lens lining up the distance window and AF controls. **For final placement pull the window for the slightly away from the lens and adjust to the left or right.**

### ***Piece 7***

Slide on piece 7 by aligning the alignment notch with the alignment mark on the lens.

### ***Rotating Lens Collar***

The LensCoat® Sigma 150-600s lens cover kit includes a strip of neoprene with adhesive tape applied to the back for the rotating lens collar. Cutout the desired length for the parts of the lens collar you want to cover. Cut the longest piece first. After all the cutting is done then remove the adhesive tape backing by carefully folding back a small corner and apply to the lens collar.

### ***Zoomed Lens Barrel***

The LensCoat® Sigma 150-600s lens cover kit includes an optional piece that can be affixed to the lens via the Velcro strip **ONLY** when the lens is fully extended

LensCoat.com®  
80 Throckmorton Street  
Freehold, NJ 07728