



LensCoat® Sony FE 300 f2.8 GM OSS INSTRUCTIONS

Piece 1- Lens Hood Cover

Remove the lens hood cover from the lens. Piece 1 has a hole at one end of the cover to accommodate for the lens hood-locking switch

Remove the tripod mount foot from the rotating lens collar. This will allow for easy installation of pieces 2, 3, 4,5. You can also put sections 2,3,4,5 and 6 on by looping the pieces around the lens foot and over the top of the lens where it mounts to the camera.

Piece 2

After removing the tripod mount foot slide piece 2 down to the front of the lens. Line up the holes at the rear of the section with the lens function buttons.

Piece 3

Slide piece 3 (narrow section) down to the function ring.

Piece 4

Slide piece 4 down past the focus ring.

Piece 5

Slide piece 5 on by **carefully lining up the AF/OSS windows and slide into. For final placement pull the window slightly away from the lens and adjust to the left or right.**

****you should be able to slide the controls through the plastic window with your finger, some people like to punch small holes in the plastic to allow for easier access, if you choose to do this be careful as it is easy to destroy the window.**

Piece 6

Slide piece 6 over the rotating collar lining up the holes for the tension knob, lens foot and straps.

Piece 7

Slide piece 7 over the last section of the lens.

LensCoat.com®
80 Throckmorton Street
Freehold, NJ 07728