



LensCoat® Canon RF 100-500 f/4-7.1 L IS INSTRUCTIONS

Piece 1- Lens Hood Cover

Remove the lens hood cover from the lens. Carefully slide and stretch the lens cover into place.

Piece 2

Remove rotating collar foot for easier placement of piece 2-5, stretch and slide piece 2 down the lens to the zoom ring.

Piece 3

Slide piece 3 down the lens to the zoom tension ring.

Piece 4

Slide piece 4 on to just before the tension ring lining up the window for the AFI/S controls. **For final placement pull the window for the slightly away from the lens and adjust to the left or right.**

Piece 5

Slide piece 5 down the lens to the focus ring.

Piece 6

Slide piece 6 on to the control ring.

Optional Piece for when not using Rotating Collar

Piece 5b

If you are not using the lens the rotating lens collar you can slide piece 5b over the section where the rotating collar was.

Rotating Lens Collar

The LensCoat® Canon RF 100-500 IS lens cover kit includes a strip of neoprene with adhesive tape applied to the back for the rotating lens. Cutout the desired length for the parts of the lens collar you want to cover. Cut the longest piece first. After all the cutting is done then remove the adhesive tape backing by carefully folding back a small corner and apply to the lens collar.

Zoom Sleeve

The LensCoat kit for the Canon RF 100-500 IS includes an optional sleeve to cover the barrel that would be exposed when zooming. With the lens shade off carefully stretch the elastic over the front of the lens onto piece 2 and the end of the lens barrel. As you zoom in the sock will stretch and when it's zoomed out it will slightly bunch up.

LensCoat.com®
80 Throckmorton Street
Freehold, NJ 07728