



LensCoat® Fuji XF 100-400mm f/4.5-5.6 R LM OIS WR INSTRUCTIONS

Piece 1 Lens Hood Cover

Remove the lens hood cover from the lens. Carefully slide and stretch the lens cover into.

Remove the tripod mount foot from the rotating lens collar. This will allow for easy installation of pieces 2-5.

Piece 2

After removing the tripod mount foot slide piece 2 down toward the end of the lens past the retracting barrel.

Piece 3

Slide piece 3 down onto the focus ring.

Piece 4

Slide piece 4 down onto the zoom ring **lining up the windows for the lock switch.**

Piece 5

Slide piece 5 down onto the aperture ring.

Piece 6- Window piece

Slide piece 6 on by **carefully lining up the limiter, AF and OIS window and slide into place. For final placement pull the distance scale window slightly away from the lens and adjust to the left or right.**

Rotating Lens Collar

The LensCoat® Fuji 100-400 lens cover kit includes one strip of neoprene with adhesive tape applied to the back. Cut out the desired length for the parts of the lens collar you want to cover. Cut the longest piece first. After all the cutting is done then remove the adhesive tape backing by carefully folding back a small corner and apply to the lens collar.

Zoomed Lens Barrel

The LensCoat® Fuji 100-400 lens cover kit includes an optional piece that can be affixed to the lens via the Velcro strip **ONLY** when the lens is fully extended

LensCoat.com®
80 Throckmorton Street
Freehold, NJ 07728